



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification <sup>6</sup> : G01V 15/00	A1	(11) International Publication Number: WO 96/31790 (43) International Publication Date: 10 October 1996 (10.10.96)
(21) International Application Number: PCT/GB96/00823 (22) International Filing Date: 3 April 1996 (03.04.96) (30) Priority Data: 9506909.2 4 April 1995 (04.04.95) GB (71) Applicant (for all designated States except US): SCIENTIFIC GENERICS LIMITED (GB/GB); Harston Mill, Harston, Cambridge CB2 5NH (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): DAMES, Andrew, Nicholas (GB/GB); 74 De Freville Avenue, Cambridge CB4 1HU (GB). (74) Agents: ABRAMS, Michael, John et al.; Haseltine Lake & Co., Hazlitt House, 28 Southampton Buildings, Chancery Lane, London WC2A 1AT (GB).	(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: SPATIAL MAGNETIC INTERROGATION

## (57) Abstract

Magnetic tags or markers are disclosed, together with a variety of techniques by means of which such tags may be interrogated. In one aspect, the magnetic marker or tag which is characterised by carrying a plurality of discrete magnetically active regions in a linear array. In another aspect, the invention provides a method of interrogating a magnetic tag or marker within a pre-determined interrogation zone, the tag comprising a high permeability magnetic material, for example to read data stored magnetically in the tag or to use the response of the tag to detect its presence and/or to determine its position within the interrogation zone, characterized in that the interrogation process includes the step of subjecting the tag sequentially to: (1) a magnetic field sufficient in field strength to saturate the high permeability magnetic material, and (2) a magnetic null as herein defined. Applications of such techniques are described, *inter alia*, in relation to (a) identifying articles to which tags are attached; (b) accurate determination of position, as in the location of surgical probes; and (c) totalisation of purchases, where each item carries a tag coded with data representing its nature and its price.

## Signals from tag at different positions with respect to null plane



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

-1-

SPATIAL MAGNETIC INTERROGATION

This invention relates to the exploitation of magnetic properties in a range of practical techniques, and utilises a new technique of spatial magnetic interrogation in conjunction with a magnetic marker or identification tag. More particularly, but not exclusively, the invention relates to methods of determining the presence and/or the location of a magnetic marker or tag within an interrogation zone; to methods of identifying a magnetic tag (e.g. identifying a given tag in order to discriminate that tag from others); to systems for putting these methods into practice; to magnetic tags for use in such methods and systems; and to the storage of data in such tags, and the subsequent remote retrieval of data from such tags.

It should be understood that the terms "tag" and "marker" are used herein interchangeably; such devices may be used in many different applications and, depending on the magnetic qualities of the device, may serve to denote (a) the mere presence of the tag (and hence that of an article to which the tag is attached); or (b) the identity of the tag (and hence that of an article to which it is attached); or they may serve to define the precise position of the tag with respect to predetermined co-ordinates (and hence that of an article to which it is attached); or they may serve to provide access codes (e.g. for entry into secure premises; or for ticketing purposes, e.g. on public transport networks); or they may serve generally to discriminate one article or set of articles from other articles.

In addition, the terms "ac field" and "DC field" are used herein to denote magnetic fields whose

-2-

characteristics are, respectively, those associated with an electrical conductor carrying an alternating current (ac) or a direct current (DC).

5       The tags, methods and systems of this invention have a wide variety of applications as indicated above. These include (but are not restricted to) inventory control, ticketing, automated shopping systems, monitoring work-in-progress, security tagging, access  
10 control, anti-counterfeiting, and location of objects (in particular the precise positioning of workpieces [e.g. probes in surgery]).

#### Prior Art

15

There are a number of passive data tag systems currently available. The most widely-used is based on optically-read printed patterns of lines, popularly known as barcodes. The tag element of such systems is  
20 very low-cost, being typically just ink and paper. The readers are also relatively low cost, typically employing scanning laser beams. For many major applications the only real drawback to barcodes is the need for line-of-sight between the reader and the tag.

25

For applications where line-of-sight is not possible, systems not employing optical transmission have been developed. The most popular employ magnetic induction for coupling between the tag and the  
30 interrogator electronics. These typically operate with alternating magnetic fields in the frequency range of 50kHz to 1MHz, and generally employ integrated electronic circuits ("chips") to handle receive and transmit functions, and to provide data storage and  
35 manipulation. In order to avoid the need for a battery, power for the chip is obtained by

-3-

rectification of the interrogating signal received by an antenna coil. In order to increase the power transferred, and to provide discrimination against unwanted signals and interference, the coil is usually  
5 resonated with a capacitor at the frequency of the interrogation signal carrier frequency. A typical product of this type is the TIRIS system manufactured by Texas Instruments Ltd.

10 Other multi-bit data tag systems have employed conventional h.f. radio technology, or technologies based on surface acoustic waves or magnetostriction phenomena.

15 The Invention

The present invention involves, *inter alia*, the use of a new type of passive data tag system which employs small amounts of very high-permeability  
20 magnetic material, and a scanned magnetic field for interrogation. Since the magnetic material can be in the form of a thin foil, wire or film, it can be bonded directly to a substrate, e.g. paper or a plastics material, to form self-supporting tags.

25 Alternatively, the magnetic material may be incorporated into the structure of an article with which the tag is to be associated; thus a tag may be formed *in situ* with the article in question by applying  
30 the magnetic material to the surface of the article, or by embedding the magnetic material within the body of the article.

The invention exploits magnetic fields which  
35 contain a "magnetic null" - this term is used herein to mean a point, line, plane or volume in space at or

-4-

within which the component of the magnetic field in a given linear direction is zero. The volume in space over which this condition is met can be very small - and this gives rise to certain embodiments of the invention in which precise position is determined. Typically the magnetic null will be extant over a relatively small linear range. It should be understood that, where there is a magnetic null, it is possible (and is often the case) that the magnetic field component in a direction orthogonal to the given linear direction will be substantial. In some embodiments of this invention, such a substantial orthogonal field is desirable.

One way of creating the magnetic null is to employ opposing magnetic field sources. These may be current-carrying coils of wire, or permanent magnets (these being well suited to small-scale systems), or combinations of coil(s) and permanent magnet(s). It is also possible to exploit the magnetic nulls which exist in specific directions when a single coil or permanent magnet is used.

For large scale applications, the magnetic field sources are preferably coils carrying direct current.

The invention also utilises the relative movement between a magnetic marker and an applied magnetic field in order to effect passage over of the marker of the magnetic null. This can be achieved by moving the marker with respect to the applied magnetic field, or by holding the marker in a fixed position while the magnetic field is scanned over it. Generally, the invention exploits the difference between the magnetic behaviour of the marker in (i) a zero field (at the magnetic null), and (ii) in a high, generally

-5-

saturating, magnetic field.

Tags of this Invention

5        according to one aspect of the present invention  
there is provided a magnetic marker or tag which is  
characterised by carrying a plurality of discrete  
magnetically active regions in a linear array. The  
discrete magnetically active regions may be supported  
10 on a substrate, e.g. paper or a plastics material, or  
they may be self-supporting. Alternatively, the  
magnetic elements may be incorporated directed into or  
onto articles during manufacture of the articles  
themselves. This is appropriate, for example, when the  
15 articles are goods, e.g. retail goods, which carry the  
tags for inventory purposes; or when the articles are  
tickets or security passes.

A tag as defined above can also be formed from a  
20 continuous strip of high permeability material,  
discrete regions of which have their magnetic  
properties permanently or temporarily modified. It  
will be appreciated that such a process can begin with  
a high permeability strip selected regions of which are  
25 then treated so as to modify their magnetic properties,  
generally by removing or reducing their magnetic  
permeability; or with a strip of high permeability  
magnetic material accompanied by a magnetisable strip  
positioned close to the high permeability magnetic  
30 material, e.g. overlying it or adjacent to it, selected  
regions of which are magnetised. In relatively simple  
embodiments, each magnetically active region has the  
same magnetic characteristics; in more complex  
embodiments, each magnetically active region can  
35 possess a different magnetic characteristic, thus  
making it possible to assemble a large number of tags

-6-

each with unique magnetic properties and hence with a unique magnetic identity and signature (when processed by a suitable reader device).

5        Because the invention utilises relative movement between a tag and an applied magnetic field, it will be appreciated that there will be a correspondence between the time domain of output signals from a tag reading device and the linear dimensions of the magnetically  
10    active regions of a tag and of the gaps between the magnetically active regions. In this sense, the active regions and the gaps between them function analogously to the elements of an optical bar code (black bar or white gap between adjacent bars). It follows from this  
15    that, just as variability of magnetic characteristics in the active regions can be used to generate part of a tag "identity", so can the linear spacing between adjacent magnetically active regions. It will readily be understood that a vast number of tags, each with its  
20    own unique identity, can thus be produced in accordance with this invention.

Although the tags have been described as possessing a linear array of magnetically active  
25    regions, the tags may in fact have two or more such linear arrays. These may be disposed mutually parallel, or mutually orthogonal, or in any desired geometrical arrangement. For simplicity of reading such tags, arrays which are parallel and/or orthogonal  
30    are preferred.

Appropriate techniques for manufacturing the tags of this invention are well-known in conventional label (i.e. magnetic marker) manufacture. Suitable magnetic  
35    materials are also well-known and widely available; they are high-permeability materials which preferably



-7-

have an extrinsic relative permeability of at least 10'. The coercivity of the magnetic material will depend on the tag's intended use. The magnetic material is preferably in the form of a long thin strip or of a thin film; these formats avoid major internal demagnetisation effects. Suitable strip materials are readily available from commercial suppliers such as Vacuumschmeltze (Germany), Allied Signal Corp. (USA), and Unitika (Japan). Thin film material currently manufactured in high volume by IST (Belgium) for retail security tag applications is also suitable for use in this invention.

#### Detection/Identification Methods

As well as the tags defined above, the present invention provides a variety of useful methods for detecting the presence of a magnetic marker and/or for identifying such a marker. While in many cases these methods will be intended for use in conjunction with the tags of the invention, this is not a necessary prerequisite in the methods of the invention.

According to a second aspect of the invention, there is provided a method of interrogating a magnetic tag or marker within a predetermined interrogation zone, the tag comprising a high permeability magnetic material, for example to read data stored magnetically in the tag or to use the response of the tag to detect its presence and/or to determine its position within the interrogation zone, characterised in that the interrogation process includes the step of subjecting the tag sequentially to: (1) a magnetic field sufficient in field strength to saturate the high permeability magnetic material, and (2) a magnetic null as herein defined.

- 8 -

Preferably the magnetic null is caused to sweep back and forth over a predetermined region within the interrogation zone. The scanning frequency (i.e. the sweep frequency of the magnetic null) is preferably  
5 relatively low, e.g. 1 - 500Hz. Conveniently, the field pattern is arranged so that (a) said magnetic null lies in a plane; and (b) the saturating field occurs adjacent to said plane.

10

According to a third aspect of this invention, there is provided a method of determining the presence and/or the position of a magnetic element within a predetermined interrogation zone, the magnetic element  
15 having predetermined magnetic characteristics, which method is characterised by the steps of: (1) establishing within said interrogation zone a magnetic field pattern which comprises a relatively small region of zero magnetic field (a magnetic null) contiguous  
20 with regions where there is a magnetic field sufficient to saturate the, or a part of the, magnetic element (the saturating field), said relatively small region being coincident with a region through which the magnetic element is passing, or can pass, or is  
25 expected to pass; (2) causing relative movement between said magnetic field and said magnetic element such that said magnetic null is caused to traverse at least a part of the magnetic element in a predetermined manner; and (3) detecting the resultant magnetic response of  
30 the magnetic element during said relative movement.

According to a fourth aspect of the present invention, there is provided a method of identifying a magnetic element which possesses predetermined magnetic  
35 characteristics, which method is characterised by the steps of: (1) subjecting the magnetic element to a

-9-

first magnetic field which is sufficient to induce magnetic saturation in at least a part of the magnetic element; (2) next subjecting the magnetic element to conditions of zero magnetic field (i.e. a magnetic null), the zero field occupying a relatively small volume and being contiguous with said first magnetic field; (3) causing relative movement between the applied magnetic field and said magnetic element such that said magnetic null is caused to traverse at least a part of the magnetic element in a predetermined manner; and (4) detecting the resultant magnetic response of the magnetic element during said relative movement.

15 In the identification method defined above, the magnetic element is advantageously caused to traverse an interrogation zone within which the required magnetic conditions are generated.

20 In a fifth aspect, the invention provides a method of identifying a magnetic element, the magnetic element having predetermined magnetic characteristics, which method is characterised by the steps of: (1) causing the magnetic element to enter an interrogation zone  
25 within which there is established a magnetic field pattern which comprises a relatively small region of zero magnetic field (a magnetic null) contiguous with regions where there is a magnetic field sufficient to saturate the, or a part of the, magnetic element (the saturating field); (2) causing the magnetic element to  
30 be moved through the saturating field until it reaches the magnetic null; (3) causing relative movement between said magnetic field and said magnetic element such that said magnetic null is caused to traverse at  
35 least a part of the magnetic element in a predetermined manner; and (4) detecting the resultant magnetic

-10-

response of the magnetic element during said relative movement.

The relative movement between the magnetic element  
5 and the magnetic field may advantageously be produced  
by sweeping the applied magnetic field over the  
magnetic element. Alternatively, the relative movement  
can be achieved by the application of an alternating  
magnetic field to a generally static magnetic field  
10 pattern.

In carrying out the methods defined above,  
preferred embodiments of the magnetic element are  
either elongate, and the magnetic null is then arranged  
15 to extend along the major axis of said magnetic  
element; or they are in the form of a thin film, in  
which case the magnetic null is arranged to extend to  
be aligned with the axis of magnetic sensitivity of the  
thin film material.

20  
The magnetic field or field pattern utilised in  
the methods defined above may be established by the  
means of two magnetic fields of opposite polarity.  
This can conveniently be achieved by use of one or more  
25 coils carrying direct current; or by the use of one or  
more permanent magnets; or by a combination of coil(s)  
and magnet(s).

Where a coil is used, it may be arranged to carry  
30 a substantially constant current so as to maintain the  
magnetic null at a fixed point. Alternatively, the  
coil(s) carry/carries a current whose magnitude varies  
in a predetermined cycle so that the position of the  
magnetic null is caused to oscillate in a predetermined  
35 manner. We describe this as a "flying null". A  
similar arrangement can be used to give a flying null

-11-

when both a coil or coils and a permanent magnet are used.

According to a further aspect of the present invention, there is provided a method of determining the presence and/or the position of a magnetic element, which is characterised by the steps of: (1) applying a magnetic field to a region where the magnetic element is, or is expected to be, located, said magnetic field comprising two opposed field components, generated by magnetic field sources, which result in a null field (a magnetic null) at a position intermediate said magnetic field sources [which position is known or can be calculated]; (2) causing relative movement between said magnetic field and said magnetic element; and (3) detecting the resultant magnetic response of the magnetic element during said relative movement.

Relative movement between the magnetic field and the magnetic element may be achieved by applying a relatively low amplitude alternating magnetic field superimposed on the DC field. Typically, such a low amplitude alternating magnetic field has a frequency in the range from 10Hz to 100kHz, preferably from 50Hz to 50kHz, and most advantageously from 500Hz to 5kHz.

In one embodiment, the coils carry a substantially constant current so as to maintain the magnetic null at a fixed point. In another embodiment, the coils carry a current whose amplitude varies in a predetermined cycle so that the position of the magnetic null is caused to oscillate in a predetermined manner.

In the methods according to this invention, detection of the magnetic response of the magnetic element advantageously comprises observation of

-12-

harmonics of the applied AC field which are generated by the magnetic element as its magnetisation state is altered by passing through the magnetic null.

5 As indicated above, the system operates with a zero or very low frequency scanning field, and an HF (high frequency) in the range 50Hz - 50kHz. This allows for good signal penetration through most materials including thin metal foils. In addition,  
10 international regulations allow high fields for transmission at these low frequencies.

Preferred embodiments of the invention provide a multi-bit data tag system which employs low-frequency  
15 inductive magnetic interrogation, and avoids the need for complex, expensive tags.

According to another aspect of the present invention, there is provided a method of coding and/or  
20 labelling individual articles within a predetermined set of articles by means of data characteristic of the articles, e.g. article price and/or the nature of the goods constituting the articles, which method is characterised by applying to each article a magnetic  
25 tag or marker carrying a predetermined arrangement of magnetic zones unique to that article or to that article and others sharing the same characteristic, e.g. article price or the nature of the goods constituting the article, said magnetic tag or marker  
30 being susceptible to interrogation by an applied magnetic field to generate a response indicative of the magnetic properties of the tag or marker and hence indicative of the nature of the article carrying the magnetic tag or marker.

35

#### Fundamentals of the Invention

-13-

Before describing further embodiments, it will be helpful to explain some fundamental aspects of the invention giving reference, where appropriate, to relatively simple embodiments.

5

A key aspect of the invention is the form of the magnetic field created in the interrogation zone; as will become apparent later, this field allows very small spatial regions to be interrogated. The means  
10 for generating this magnetic field will be termed hereinafter an "interrogator". In one simple form, the interrogator consists of a pair of closely-spaced identical coils arranged with their axes coincident. The coils are connected together such that their  
15 winding directions are opposed in sense, and a DC current is passed through them. This causes opposing magnetic fields to be set up on the coils axis, such that a position of zero field - a magnetic null - is created along the coil axis, mid-way between the coils.  
20 The level of current in the coils is such as to heavily saturate a small sample of high permeability magnetic material placed at the centre of either of the two coils. A much lower amplitude AC current is also caused to flow in opposite directions through the two  
25 coils, so that the AC fields produced sum together mid-way between the coils. This can easily be arranged by connecting a suitable current source to the junction of the two coils, with a ground return. The frequency of this AC current may typically be about 2 kHz, but its  
30 value is not critical, and suitable frequencies extend over a wide range. This AC current generates the interrogating field which interacts with a magnetic tag to generate a detectable response. Another effect of this AC current is to cause the position of zero  
35 field - the magnetic null - to oscillate about the mid-way position along the coils axis by a small amount

-14-

(this is a wobble or oscillation rather than an excursion of any significant extent).

In addition, a further, low frequency AC current  
5 may be fed to the coils so as to generate a low frequency scanning field (which may be zero). The frequency of the scanning field (when present) should be sufficiently low to allow many cycles of the relatively high frequency interrogation field to occur  
10 in the time that the magnetic null region passes over the tag; typically, the frequency ratio of interrogating field ( $\omega_i$ ) to the scanning field ( $\omega_s$ ) is of the order of 100:1, although it will be appreciated that this ratio can vary over a considerable range  
15 without there being any deleterious effect on the performance of the invention.

When a tag containing a piece of high-permeability magnetic material is passed along the coils axis  
20 through the region over which oscillation of the magnetic zero plane occurs, it will initially be completely saturated by the DC magnetic field. It will next briefly be driven over its B-H loop as it passes through the zero field region. Finally it will become  
25 saturated again. The region over which the magnetic material is "active", i.e. is undergoing magnetic changes, will be physically small, and is determined by the amplitude of the DC field, the amplitude of the AC field, and the characteristics of the magnetic  
30 material. This region can easily be less than 1 mm in extent. If the level of the alternating field is well below that required to saturate the magnetic material in the tag, then harmonics of the AC signal will be generated by the tag as it enters the zero field region  
35 of interrogator field and responds to the changing field. As the tag straddles the narrow zero field



-15-

region the tag will be driven on the linear part of its B-H loop, and will interact by re-radiating only the fundamental interrogation frequency. Then, as the tag leaves the zero field region, it will again emit  
5 harmonics of the interrogation field frequency. A receiver coil arranged to be sensitive to fields produced at the zero field region, but which does not couple directly to the interrogator coils, will receive only these signals. The variation of these signals  
10 with time as the tag passes along the coils axis gives a clear indication of the passage of the ends of the magnetic material through the zero field region.

It will be appreciated that because the  
15 interrogation zone can be very narrow, each individual piece of magnetic material can be distinguished from its neighbours, from which it is separated by a small distance. Naturally, the magnetic material will be selected to suit the particular application for which  
20 the tag is intended. Suitable magnetic materials are commercially available, as described hereinbefore.

If a tag containing a number of zones or pieces of magnetic material placed along the axis of the label is  
25 now considered, it will be appreciated that as each zone or piece of magnetic material passes through the zero-field region, its presence and the positions of its ends can be detected. It then becomes a simple matter to use the lengths and spacings of individual  
30 zones or pieces of magnetic material to represent particular code sequences. Many different coding schemes are possible: one efficient arrangement is to use an analogue of the coding scheme used for optical barcodes, where data is represented by the spacing and  
35 widths of the lines in the code.

-16-

The system so far described allows for the scanning of a single-axis tag (e.g. a wire or a thin strip of anisotropic material, having a magnetic axis along its length) as it physically moves through the coil assembly. It will be appreciated that relative movement between the tag and the interrogating field can be achieved either with the field stationary and the tag moving, or vice versa. If required, the arrangement can be made self-scanning, and thus able to interrogate a stationary tag, e.g. by modulating the d.c. drive currents to the two interrogator coils, so that the zero field region scans over an appropriate portion of the axis of the coils. The extent of this oscillation needs to be at least equal to the maximum dimension of a tag, and should preferably be considerably greater, to avoid the need for precise tag positioning within the interrogation zone.

By using extra coils arranged on the 2 axes orthogonal to the original, tags in random orientations can be read by sequentially field scanning. This involves much greater complexity in the correlation of signals from the three planes, but because of the very high spatial resolution available would be capable of reading many tags simultaneously present in a common interrogation volume. This is of enormous benefit for applications such as tagging everyday retail shopping items, and, for example, would allow automated price totalisation of a bag of shopping at the point of sale. Thus the invention has applicability to the price labelling of articles and to point-of-sale systems which generate a sales total (with or without accompanying inventory-related data processing).

35

The size of a simple linear tag is dependent on

-17-

the length of the individual elements, their spacing and the number of data bits required. Using strips of the highest permeability material commercially available, such as the "spin-melt" alloy foils  
5 available from suppliers such as Vacuumschmelze (Germany) and Allied Signal (USA), the minimum length of individual elements which can be used is probably of the order of a few millimetres. This is because the extrinsic permeability will be dominated by shape  
10 factors rather than by the very high intrinsic permeability (typically  $10^4$ ), and shorter lengths may have insufficient permeability for satisfactory operation.

15 For this reason it is attractive to use very thin films of high permeability magnetic material. Provided it is very thin, (ideally less than  $1\mu\text{m}$ ), such material can be cut into small 2 dimensional pieces (squares, discs etc) with areas of just  $20\text{ mm}^2$  or less, yet still  
20 retain high permeability. This will enable shorter tags than possible with elements made from commercially available high-permeability foils. Suitable thin film materials are available commercially from IST (Belgium).

25 An extension to this type of programming can also be used to prevent the composite tag producing an alarm in a retail security system (such an alarm would be a false indication of theft, and would thus be an  
30 embarrassment both to the retailer and to the purchaser). If different regions of the tag are biased with different static field levels, they will produce signals at different times when they pass through retail security systems. This will complicate the  
35 label signature in such systems and prevent an alarm being caused. In the present invention, the reading

-18-

system will be able to handle the time-shifted signals caused by such magnetic biasing.

Thus far tag coding has been described on the basis of physically separated magnetic elements. It is not essential, however, to physically separate the elements; programming of data onto a tag may be accomplished by destroying the high-permeability properties of a continuous magnetic element in selected regions thereof. This can be done, for example, by local heating to above the recrystallisation temperature of the amorphous alloy, or by stamping or otherwise working the material. Of even more importance is the ability to magnetically isolate regions of a continuous element of high permeability material by means of a magnetic pattern stored on an adjacent bias element made from medium or high coercivity magnetic material. Such a composite tag could then be simply coded by writing a magnetic pattern onto the bias element using a suitable magnetic recording head. If required, the tag could then be erased (by de-gaussing with an AC field) and re-programmed with new data.

The scheme described can also be extended to operate with tags storing data in two dimensions. This allows for much more compact tags, since as well as being a more convenient form, a tag made up from an  $N \times N$  array of thin-film patches has much more coding potential than a linear array of the same number of patches. This is because there are many more unique patch inter-relationships that can be set up in a given area.

Further Embodiments

Use of Spatial Magnetic Scanning for Position Sensing

In addition to interrogating space to read data tags, this new technique of moving planes of zero field through space (or moving things through the planes) can be used to provide accurate location information for small items of high permeability magnetic material.

Thus, according to another aspect, the invention provides a method of determining the precise location of an object, characterised in that the method comprises: (a) securing to the object a small piece of a magnetic material which is of high magnetic permeability; (b) applying to the region in which said object is located a magnetic field comprising two opposed field components, generated by magnetic field sources, which result in a null field at a position intermediate said magnetic field sources; (c) applying a low amplitude, high frequency interrogating field to said region; (d) causing the position of the null field to sweep slowly back and forth over a predetermined range of movement; (e) observing the magnetic interaction between said applied magnetic field and said small piece of magnetic material; and (f) calculating the position of the object from a consideration of said magnetic interaction and from the known magnetic parameters relating to said applied field and to said small piece of magnetic material. Advantageously, the small piece of high permeability magnetic material is in the form of a thin foil, a wire or a thin film.

This aspect of the invention is of particular interest when the object whose location is to be determine is a surgical instrument, for example a surgical probe or needle. The invention allows precise

-20-

determination of the location of, for example, a surgical probe during an operation.

This technique is ideal for accurate location of very small markers within relatively confined volumes; it can separately resolve multiple markers. It also displays low sensitivity to extraneous metal objects.

The magnetic tag or marker can typically be a 1 cm length (longer if desired) of amorphous wire (non-corrosive, diameter 90 micron or less) similar to that used in EAS tags or, with suitable process development, a short length (eg 1 cm) of a needle sputter-coated with a thin layer of soft magnetic material.

15

In use around the head of a patient, resolution to 0.1 mm with the described markers can be achieved. accuracy should also have the potential to approach this value if some precautions about calibration and use of other magnetic materials are observed, but for optimum performance a rigid but open structure close to the head would be desired. The magnetic field levels employed will be lower than those generated by every day magnets (eg kitchen door catches etc).

25

This technique has particular application to brain surgery, where there is the requirement to locate the position of probes in three dimensions and with high precision. It is therefore possible, in accordance with this invention, to use small magnetic markers on such probes or needles. In this case, a key advantage is that the signal from the marker need only be detected and resolved in time; the resolution is determined by the location of the zero field plane, not by the signal to noise ratio of the detected marker signal. This permits a very small marker to be used.

35

-21-

A single axis position sensor may be implemented with a set of coils similar to the tag reading system described above. This comprises: a pair of opposed coils carrying DC current to generate a DC field  
5 gradient; a means of applying a relatively uniform low level AC field to drive the marker in and out of saturation in the small region where the DC field is close to zero; and a means of applying a relatively uniform DC field of variable strength and polarity to  
10 move the location of the plane of zero DC field around the volume to be interrogated.

An anisotropic marker - i.e. one having a preferential axis of magnetisation - resolves the  
15 magnetic field along its length. Such a marker can be obtained, for example, by using a long, thin element of a magnetic material or by suitable treatment of an area of magnetic material having a much lower aspect ratio, e.g. by longitudinally annealing a generally  
20 rectangular patch of a spin-melt magnetic material. In the context of the single axis position sensor under discussion there are five degrees of freedom ( $x, y, z$  and two angles (rotation of the marker about its axis has no effect)). Three orthogonal complete sets of coils  
25 can capture sufficient information by doing three scans of the uniform DC field on each of the sets of coils in turn. The first scan with no field from the other sets, the second with a uniform DC field from one of the other sets, and the third with DC field from the  
30 other set. This gives nine scans in all; these may be represented as in the following table, in which the magnetic field sources are identified as a, b and c and the scans are numbered from 1-9 (scanning order being of no significance):

35

-22-

Orthogonal field source	1	2	3	4	5	6	7	8	9
a	ON	ON	ON	OFF	OFF	ON	OFF	OFF	ON
b	OFF	ON	OFF	ON	ON	ON	OFF	ON	OFF
c	OFF	OFF	ON	OFF	ON	OFF	ON	ON	ON

The only information required from each scan is the position of the centre of the harmonic output from the marker within that scan. These nine DC field values can then be converted into the xyz-theta-phi co-ordinates of the marker. To start with, the system can simply be used by holding the marker in the desired position before the head is put into the coils; and then when the head is placed in the coils the marker can be moved until the same signals are obtained.

An alternative to sequential interrogation which has the advantage of requiring less time to scan the region of interest is to rotate the magnetic field gradient continuously so as to scan all directions of interest. This can be accomplished by driving three sets of coils with appropriate continuous waveforms. For example, a suitable scanning field will be created if coils in the x, y and z planes are driven with currents  $I_x$ ,  $I_y$  and  $I_z$  given by the equations:

$$\begin{aligned}
 I_x &= \cos \omega_a t (A \cos \omega_b t - \sin \omega_b t \cdot \sin \omega_c t) \\
 &\quad - \sin \omega_a t \cdot \cos \omega_c t \\
 I_y &= \sin \omega_a t (A \cos \omega_b t - \sin \omega_b t \cdot \sin \omega_c t) \\
 &\quad + \cos \omega_a t \cdot \cos \omega_c t
 \end{aligned}$$

$$I_z = A \sin \omega_b t + \cos \omega_b t \cdot \sin \omega_c t$$

where:  $\omega_a$  = overall frequency of rotation of



-23-

applied magnetic field

$\omega_b$  = null scanning frequency

$\omega_c$  = interrogation frequency

A = amplitude ratio  $\omega_b : \omega_c$ .

5

Typical (but non-limiting) values of these parameters are: A  $\approx$  10;

frequency ratio  $\omega_b : \omega_c \approx 1 : 10$ ; and

frequency ratio  $\omega_b : \omega_c = 1 : 400$ .

10

#### Description of the Drawings

The invention will now be illustrated with reference to the accompanying drawings, in which:

15 FIGURE 1 illustrates the fundamental elements of a tag reading system of the invention;

FIGURE 2 is a circuit diagram illustrating one mode of generating the desired magnetic field pattern with the arrangement of Fig. 1;

20 FIGURE 3 relates the magnetic response of a tag to its position within the reading system of Fig. 1;

FIGURE 4 illustrates where magnetic nulls occur with a permanent magnet;

25 FIGURE 5 illustrates an embodiment of the invention which utilises a coil and a permanent magnet to generate the desired field pattern;

FIGURE 6 illustrates an embodiment of the invention which utilises a pair of permanent magnets to generate the desired field pattern;

30 FIGURE 7 illustrates an embodiment of the invention which utilises a plurality of permanent magnets disposed in an annular array with a coil to generate the desired field pattern;

35 FIGURE 8 is a schematic circuit diagram for one embodiment of a tag interrogator in accordance with the invention;

-24-

FIGURE 9 illustrates a selection of tags in accordance with this invention; and

FIGURE 10 illustrates an embodiment of the invention as applied to surgical operations.

5

Referring to Figure 1, a schematic arrangement is shown in which a tag 1 is positioned mid-way between two coils Tx1 and Tx2. The tag is of the type shown in Figure 9a, i.e. a simple linear tag carrying a

10 plurality of magnetic elements each of which is a high-permeability magnetic alloy material, for example Vacuumschmelz 6025 spin melt ribbon having an intrinsic permeability of about  $10^5$ . The reader will appreciate that the values given in this description

15 for the various parameters associated with the elements shown in Figure 1 are given merely by way of example, and illustrate one working embodiment. The values of these parameters will inevitably vary according to the overall size of the system and its intended function.

20 The magnetic elements which constitute the discrete magnetically active regions of the tag have dimensions 10mm x 1mm x 25 microns; the spacing between adjacent elements is 1mm. The two coils are spaced apart by approximately 20cm and each comprise 450 turns of

25 0.56mm copper wire wound in a square configuration typically 45cm x 45cm. Each coil has a resistance of 6 $\Omega$  and an inductance of 100mH. Each of the coils Tx1 and Tx2 carries a direct current  $I$  superimposed upon which is a smaller alternating current  $i$ ; typically,

30 the direct current  $I$  is of the order of 3A while the superimposed alternating current  $i$  is of the order of 50mA. The alternating current  $i$  is of relatively high frequency, typically about 2kHz.

35 With a system such as that just described, the alternating and direct currents in the two coils

-25-

generate a magnetic field pattern in which there is a magnetic null in the direction of arrow  $x$  at points lying in a plane parallel to the two coils and mid-way between them. In Figure 1, the  $x$ - and  $y$ -coordinates of this mid-way plane are represented by the lines 2 and 3, respectively.

If a magnetic tag of this invention is passed through the two coils shown in Figure 1, travelling in direction  $x$  and generally along the longitudinal axis defined between the centre points of the two coils, it will pass through a magnetic field polarity inversion at the mid-way plane defined by coordinates 2 and 3. The change in polarity of the magnetic field comes about because the DC current flows in one sense in the first of the coils and in the opposite sense in the other of the coils, as indicated by the bold arrows in Figure 1. At the mid-way plane, the magnetic field component generated by the direct current flowing in the first coil exactly cancels the magnetic field component generated by the direct current flowing in the other coil.

As the tag travels through the centre of the first coil, it experiences a high magnetic field which is sufficient to saturate its magnetically active elements; as the field strength decreases on moving towards the mid-way plane, the magnetic material is influenced by the decreasing magnetic field in a way dictated by its hysteresis curve. In the vicinity of the magnetic null, the direction of magnetisation of the magnetic elements of the tag is reversed.

The relatively high frequency alternating current  $i$  shown in Figure 1 is identical in each of the coils Tx1 and Tx2.

-26-

The alternating current can have a frequency within a wide range, as indicated hereinbefore; a typical operating value with the arrangement of Figure 1 is about 2kHz. The effect of this relatively low amplitude alternating current is to cause the mid-way plane defined by coordinates 2, 3 to oscillate about the geometric midpoint along the longitudinal axis defined between the midpoints of the two coils. In other words, the plane containing the magnetic null oscillates or wobbles back and forth over a small spatial region at the frequency of the alternating current.

Figure 2 shows a simple circuit for providing opposed DC fields combined with AC fields. Capacitor C1 is selected to resonate with the inductance of coils Tx1 and Tx2 at the AC drive frequency; each of these coils has a resistance of 6 ohms and an inductance of 100 millihenries. A typical value for C1 is 0.1 $\mu$ F. C2 is a capacitor selected to behave as an effective short-circuit at the AC drive frequency; a typical value for this component is 22 $\mu$ F. The DC power supply will typically provide 30 volts at 3 amps; and the AC source will typically deliver an alternating current at a frequency of 2kHz at 2v rms.

Figure 3 illustrates how the magnetisation of a single magnetic element varies with time at different positions within the magnetic field pattern defined between the coils Tx1 and Tx2 of Figure 1. For ease of illustration, the oscillation of the plane containing the magnetic null is represented by the bold double-headed arrow ( $\leftrightarrow$ ) 4, the extreme positions of the plane being represented by dashed lines 5 and 6,

-27-

respectively, and the mid-point between limiting planes 5 and 6 being represented by dashed line 7. In the right hand portion of Figure 3, the applied AC field is shown varying with time between positive (H+) and negative (H-) field values. Beneath the graph of the applied AC field, there are five graphs depicting how the net magnetisation of the magnetic element varies with time in each of five geometric positions indicated to the left as Position 1, Position 2, etc. Planes 5 and 6 define the limits of regions within which magnetic field polarity reversals occur. In practice, the separation between planes 5 and 6 is typically of the order of 1 mm; for a given magnetic material, this distance can be increased or decreased at will within certain limits by varying the amplitude of the AC current and/or the DC current in the coils.

At all times, the magnetic element has a linear magnetic axis which is orthogonal to the planes 5, 6 and 7.

In Position 1, the end of the magnetic element is adjacent to plane 6; in this condition, it experiences a positive magnetic field at all times and its net magnetisation is time-invariant. In Position 2, the leading end of the element has reached the mid-way plane 7. Most of the magnetic material, however, still remains outside limiting plane 6. In consequence, the null plane is able to interact with only a portion of the magnetic material, resulting in a time-variable net magnetisation having the repeat pattern shown, i.e. a straight line positive-value portion followed by a generally sinusoidal arc which dips towards zero and then rises to its original positive value.

35

In Position 3, the magnetic material is positioned

-28-

symmetrically with respect to the mid-way plane 7. Here, the net magnetisation versus time plot consists of a sine wave whose frequency corresponds to that of the applied AC field. In Position 4, the majority of the magnetic element experiences a negative field at all times, while a smaller part of the element experiences polarity reversals; this leads to the net magnetisation versus time plot as shown. The fact that Position 4 is in effect the inverse of Position 2 is reflected in the relationship between the magnetisation plots for these two positions; as can be seen, the plot for Position 4 is effectively a mirror image of that for Position 2 but with the curved portions time-shifted.

Finally, that Position 5, all of the tag experiences the negative field, and no part of the tag experiences field polarity reversal. In consequence, the net magnetisation is time-invariant, being a constant negative value as shown.

When a tag containing such a magnetic element is passed along the coils' axis through the region of zero field, it will initially be completely saturated by the DC magnetic field. It will next briefly be driven over its B-H loop as it passes through the zero field region. Finally it will become saturated again. The portion of the traverse over which the magnetic material is "active", i.e. is undergoing magnetic changes, is physically small, and is determined by the amplitude of the DC field, the amplitude of the AC field, and the characteristics of the magnetic material. This region can easily be less than 1mm in extent. If the level of the alternating field is well below that required to saturate the magnetic material in the tag, then harmonics of the AC signal will be

-29-

generated by the tag as it enters the zero field region (Positions 1 to 2) and responds to the changing field. As the tag straddles the narrow zero field region (Position 3) the tag will be driven on the linear part  
5 of its B-H loop, and will interact by re-radiating only the fundamental interrogation frequency. Then, as the tag leaves the zero field region, (Positions 4 to 5) it will again emit harmonics of the interrogation field frequency.

10

A receiver (Rx) coil arranged to be sensitive to fields produced at the zero field region, but which does not couple directly to the interrogator (Tx) coils, will receive only these signals. Such an  
15 arrangement can be achieved by using separate Tx and Rx coils physically arranged to have low mutual coupling; or by using a single coil (having both Tx and Rx functions) together with suitable filtering in the Tx and Rx paths. The variation of these signals with time  
20 as the tag passes along the coils' axis gives a clear indication of the passage of the ends of the magnetic material through the zero field region.

The result of this interaction between the tag and  
25 the magnetic field it experiences is shown in Figure 3b. Here, the region 4 over which the magnetic null oscillates is shown on a smaller scale, and the numbered dots represent the location of the mid-point of the tag in each of Positions 1-5. The generation of  
30 a harmonic signal by the tag (illustrated by the second harmonic of the applied frequency) is apparent at positions where the tag enters the region defined by limiting planes 5 and 6, i.e. the zone where magnetic field polarity reversals occur. Because of the  
35 symmetry of the system, a single magnetic element will generate a doublet peak 8a and 8b since Positions 2 and

-30-

4 are redundant.

Referring now to Figure 4, this illustrates the lines of force (i.e. the magnetic contours) existing with a simple bar magnet. The plane X-Y which intersects the longitudinal axis of the bar magnet and which is orthogonal to the plane of the paper constitutes a magnetic null plane. Thus a magnetic element possessing a sensitive magnetic axis aligned orthogonally with respect to the null plane will experience a magnetic null as it traverses either path A-B or path C-D. Consequently a simple bar magnet can be used as part of an interrogation system to detect the presence of such a magnetic tag, or to read information carried by such a tag.

The generation of second harmonic signal can form the basis of a tag detection system. If, instead of just a single magnetic element, the tag includes a linear array of  $n$  magnetic elements, the second harmonic output from the tag will comprise  $n$  duplet peaks, each of the type shown in Figure 3b. If the size and magnetic characteristics of the magnetic elements are all the same, the peaks will have the same profile and each peak will define an envelope of constant area. The spacing between individual magnetic elements will influence the relative positions of the duplet peaks on an amplitude versus time plot. It will be appreciated that the present invention is not restricted to the use of such simple tags as just described. The use of magnetic elements of different sizes and magnetic characteristics, and with non-uniform spacing along the length of the magnetic tag, will generate more complex signal patterns which nevertheless are characteristic of the given tag construction. By varying the number, the magnetic



-31-

characteristics, and the positioning of a series of magnetic elements, it is possible to manufacture a very large number of magnetic tags each with its own unique characteristics which will accordingly generate a  
5 unique signal when used in conjunction with the system of Figures 1-3.

It will also be appreciated that the invention is not limited to observing the second harmonic of the  
10 applied alternating frequency; this particular harmonic has been selected for the purposes of illustration since it is relatively easy to generate a transmit signal (Tx output) which has no (or very little) second harmonic content, thus permitting good discrimination  
15 between the Tx signal and the response of the tag; and since it also contains a relatively high proportion of the total harmonic energy output from the tag.

Referring next to Figure 5, there is shown a  
20 schematic arrangement for a simple tag reader in accordance with this invention, the reader utilising a permanent magnet 10 and a coil 11 located adjacent to one face of the magnet. In this embodiment, a tag which is to be read can be passed along path C-D  
25 through coil 11 or along path A-B above the coil. The tags must be oriented with their magnetic axis aligned with the direction of tag movement. In Figure 5, the magnetic null plane is positioned at 12 as shown.

30 Referring next to Figure 6, the use of two permanent magnets positioned with their magnetic axes aligned and with like poles opposing one another is illustrated. Such an arrangement generates a null plane 13; the direction of tag motion required is  
35 indicated by arrows 14. Again, the magnetic axis of the tag must be aligned with the direction of movement.

-32-

Figure 7 shows a simple realisation of a tag reader head using a plurality of permanent magnets to generate a magnetic null plane. As illustrated, ten polymer-bonded ferrite magnets are disposed in an annular array with like poles facing inwards. A common transmit/receive coil L1 sits within the annulus of magnets in the manner indicated. The tag is read as it passes through the null plane in the centre of the loop of magnets.

10

Referring next to Figure 8, there is shown one embodiment of an interrogation system in accordance with this invention. This is based on the use of a single coil L1 to act as both transmitter (Tx) coil, which generates the desired magnetic field pattern, and as the receiver (Rx) coil. The system uses the second harmonic output of the tag as the basis for tag detection/identification. Circuit components C1 and L2 form a resonant trap at frequency  $2f$  to reduce signals at this frequency in the Tx output to a very low level; C2 resonates with L1 at frequency  $f$ ; and components C3, C4, L1 and L3 form a filter to pass wanted signals from the tag at frequency  $2f$  while rejecting signals at the transmitted frequency  $f$ .

25

The output obtained from this circuit passes through a low pass filter to an analogue to digital converter (ADC) and thence to a digital signal processor. These components, and in particular the signal processor, will be configured to suit the intended application of the interrogation unit. The nature of the signal processing, and the means by which it is achieved, are all conventional and therefore will not be described further here.

35

Figure 9 illustrates the basic structure of

-33-

magnetic tags in accordance with the invention. Fig. 9a shows a tag 100 which comprises a support medium 101 (e.g. paper or a plastics material) and a linear array of magnetically active regions 102, 103, 104, 105 and 106. Each magnetically active region is formed from a patch of high-permeability magnetic material (e.g. Vacuumschmeltze 6025) having its magnetic axis aligned along the length of the tag. Each patch is about 10mm<sup>2</sup> in area and is adhesively secured to the substrate 101.

10

Patches 101-105 are identical in dimensions and magnetic properties, and are uniformly spaced apart, gaps 110, 111 and 112 all being the same. The gap between patches 105 and 106, however, is larger - as though there were one patch missing at the position indicated by dotted lines at 113.

Tag 100 behaves as a six-bit tag, coded 111101 (the zero being area 113).

20

A functionally equivalent tag 120 is formed of a substrate 121 carrying magnetic elements 122-126 and having a "gap" 127; in this embodiment, the magnetic elements are in the form of a strip or wire of high-permeability magnetic material (e.g. Vacuumschmeltze 6025), typically being about 5mm long, 1mm wide and about 15 microns in thickness.

Figure 9b illustrates an alternative construction for a six-bit, laminated tag 130. This tag is coded 111101, as in Fig. 9a. Here, a continuous layer or length of high permeability magnetic material 131 (in the form of wire, strip, thin film or foil) and a substrate 133 have sandwiched between them a magnetic bias layer 132. The bias layer is magnetised in predetermined areas which influence the overlying high

35

-34-

permeability material to generate magnetically active regions indicated as 134, 135, 136, 137 and 138. Region 139 is not active, and thus constitutes a magnetic zero. When read by an interrogation system  
5 such as that of Fig. 8, the output generated by tags 100, 120 and 130 will be as shown in Figure 9d.

A more complex tag is shown in Fig. 9c. Here there are a series of parallel linear arrays of  
10 magnetically active material, generating a 4 x 4 array of sites where the magnetically active material may be present (coding as '1') or absent (coding as '0').

Figure 10 illustrates the general arrangement of  
15 three sets of coils as used in accordance with this invention for surgical applications. The three sets of coils are all mutually orthogonal and define a cavity into which the head 200 of a patient may be positioned. The first coil set consists of coils 201a and 201b; the  
20 second set consists of coils 202a and 202b; and the third set consists of coils 203a and 203b. In the drawing, two surgical probes 204 and 205 are shown schematically in position within the patient's cranium. The probes each have, at their distal ends, a magnetic  
25 tag 206, 207 such as one of those described with reference to Fig. 9 above. Because the magnetic element of the tag is only required to provide information of its presence (rather than hold extensive data), relatively simple tags are preferred. A single  
30 magnetic element of high permeability magnetic material located at the tip of the probe is sufficient. The coils are operated in the manner described in detail hereinabove. By means of the present invention, it is possible to determine the positions of the ends of the  
35 probes with high precision - and thus to carry out delicate surgical procedures with accuracy and with

-35-

minimum damage to healthy tissue.

-36-

## CLAIMS:

1. A magnetic marker or tag which is characterised by carrying a plurality of discrete magnetically active regions in a linear array.
2. A tag as claimed in claim 1, characterised in that said discrete magnetically active regions are supported on a substrate.
3. A tag as claimed in claim 1 or 2, characterised in that said discrete magnetically active regions are formed from a continuous strip of magnetisable material discrete regions of which are magnetised and the space(s) between said magnetically active regions are non-magnetised.
4. A tag as claimed in claim 1, 2 or 3, characterised in that the tag has two or more linear arrays of magnetically active regions.
5. A tag as claimed in claim 4, characterised in that the tag has two linear arrays disposed orthogonally.
6. A tag as claimed in any preceding claim, characterised in that each of the magnetically active regions is of substantially the same shape and size.
7. A tag as claimed in any preceding claim, characterised in that the spacing between each of the magnetically active regions is uniform.
8. A tag as claimed in any one of claims 1 to 6, characterised in that the spacing between each of the magnetically active regions is non-uniform.

-37-

9. A tag as claimed in any preceding claim, characterised in that it is in the form of a relatively long, thin strip having a preferential axis of magnetisation along its length.

5

10. A tag as claimed in any one of claims 1 to 9, characterised in that the magnetically active regions are formed of a thin film, spin-melt material having a preferential axis of magnetisation, the preferential axes of magnetisation being aligned within the (or each) linear array.

11. A tag as claimed in claim 9, characterised in that the preferential axes of magnetisation are generated by longitudinal annealing of the thin film, spin-melt material.

12. A method of interrogating a magnetic tag or marker within a predetermined interrogation zone, the tag comprising a high permeability magnetic material, for example to read data stored magnetically in the tag or to use the response of the tag to detect its presence and/or to determine its position within the interrogation zone, characterised in that the interrogation process includes the step of subjecting the tag sequentially to: (1) a magnetic field sufficient in field strength to saturate the high permeability magnetic material, and (2) a magnetic null as herein defined.

30

13. A method as claimed in claim 12, characterised in that said magnetic null is caused to sweep back and forth over a predetermined region within the interrogation zone.

35

14. A method as claimed in claim 12 or 13,

-38-

characterised in that (a) said magnetic null lies in a plane; and (b) the saturating field occurs adjacent to said plane.

5

15. A method of determining the presence and/or the position of a magnetic element within a predetermined interrogation zone, the magnetic element having predetermined magnetic characteristics, which method is  
10 characterised by the steps of: (1) establishing within said interrogation zone a magnetic field pattern which comprises a relatively small region of zero magnetic field (a magnetic null) contiguous with regions where there is a magnetic field sufficient to saturate the,  
15 or a part of the, magnetic element (the saturating field), said relatively small region being coincident with a region through which the magnetic element is passing, or can pass, or is expected to pass; (2) causing relative movement between said magnetic field  
20 and said magnetic element such that said magnetic null is caused to traverse at least a part of the magnetic element in a predetermined manner; and (3) detecting the resultant magnetic response of the magnetic element during said relative movement.

25

16. A method of identifying a magnetic element which possesses predetermined magnetic characteristics, which method is characterised by the steps of: (1) subjecting the magnetic element to a first magnetic field which is  
30 sufficient to induce magnetic saturation in at least a part of the magnetic element; (2) next subjecting the magnetic element to conditions of zero magnetic field (i.e. a magnetic null), the zero field occupying a relatively small volume and being contiguous with said  
35 first magnetic field; (3) causing relative movement between the applied magnetic field and said magnetic



-39-

element such that said magnetic null is caused to  
traverse at least a part of the magnetic element in a  
predetermined manner; and (4) detecting the resultant  
magnetic response of the magnetic element during said  
5 relative movement.

17. A method according to claim 16, characterised in  
that said magnetic element is caused to traverse an  
interrogation zone within which the required magnetic  
10 conditions are generated.

18. A method of identifying a magnetic element, the  
magnetic element having predetermined magnetic  
characteristics, which method is characterised by the  
15 steps of: (1) causing the magnetic element to enter an  
interrogation zone within which there is established a  
magnetic field pattern which comprises a relatively  
small region of zero magnetic field (a magnetic null)  
contiguous with regions where there is a magnetic field  
20 sufficient to saturate the, or a part of the, magnetic  
element (the saturating field); (2) causing the  
magnetic element to be moved through the saturating  
field until it reaches the magnetic null; (3) causing  
relative movement between said magnetic field and said  
25 magnetic element such that said magnetic null is caused  
to traverse at least a part of the magnetic element in  
a predetermined manner; and (4) detecting the resultant  
magnetic response of the magnetic element during said  
relative movement.

30

19. A method according to claim 15, 16, 17 or 18,  
characterised in that said relative movement is  
produced by sweeping the applied magnetic field over  
the magnetic element.

35

20. A method according to any one of claims 12 to 19,

-40-

characterised in that said magnetic element is generally elongate and in that the zero field direction of said magnetic null is arranged to extend along the major axis of said magnetic element.

5

21. A method according to any one of claims 12 to 19, characterised in that said magnetic element is in the form of a thin film and in that the zero field direction of said magnetic null is arranged to be  
10 aligned with the axis of magnetic sensitivity of the film.

22. A method as claimed in any one of claims 12 to 21, characterised in that said magnetic field or magnetic  
15 field pattern is established by the application to said spatial volume or to said interrogation zone of two magnetic fields of opposite polarity.

23. A method as claimed in claim 22, characterised in  
20 that the application of said two magnetic fields is achieved by use of one or more coils carrying direct current.

24. A method as claimed in any one of claims 12 to 23,  
25 characterised in that said magnetic field or magnetic field pattern is established by the use of one or more permanent magnets.

25. A method according to claim 23, characterised in  
30 that said coil(s) carry/carries a substantially constant current so as to maintain the magnetic null at a fixed point.

26. A method according to claim 23, characterised in  
35 that said coil(s) carry/carries a current whose magnitude varies in a predetermined cycle so that the

-41-

position of the magnetic null is caused to oscillate in a predetermined manner.

27. A method according to claim 24, characterised in  
5 that said permanent magnet(s) is or are accompanied by a coil or coils which carry or carries a current whose magnitude varies according to a predetermined cycle so that the position of the magnetic null is caused to oscillate in a predetermined manner.

10

28. A method as claimed in any one of claims 15 to 27, characterised in that said relative movement is caused by the application to said magnetic field or magnetic field pattern of an alternating magnetic field.

15

29. A method of determining the presence and/or the position of a magnetic element, which is characterised by the steps of: (1) applying a magnetic field to a region where the magnetic element is, or is expected to  
20 be, located, said magnetic field comprising two opposed field components, generated by at least one magnetic field source, which result in a null field at a predetermined position; (2) causing relative movement between said magnetic field and said magnetic element;  
25 and (3) detecting the resultant magnetic response of the magnetic element during said relative movement.

30. A method according to claim 28 or 29, characterised in that relative movement between said  
30 magnetic field and said magnetic element is caused by applying a relatively low amplitude alternating magnetic field superimposed on a DC field.

31. A method according to claim 30, characterised in  
35 that said relatively low amplitude alternating magnetic field has a frequency in the range from 10Hz to 100kHz.

-42-

32. A method according to any one of claims 12 to 31, characterised in that detection of the magnetic response of said magnetic element comprises observation of harmonics which are generated by the magnetic  
5 element from an applied AC field as its magnetisation state is altered by passing through the magnetic null.

33. A method of determining the precise location of an object, characterised in that the method comprises: (a)  
10 securing to the object a small piece of a magnetic material which is of high magnetic permeability; (b) applying to the region in which said object is located a magnetic field comprising two opposed field components, generated by magnetic field sources, which  
15 result in a null field at a position intermediate said magnetic field sources; (c) applying a low amplitude, high frequency interrogating field to said region; (d) causing the position of the null field to sweep slowly back and forth over a predetermined range of movement;  
20 (e) observing the magnetic interaction between said applied magnetic field and said small piece of magnetic material; and (f) calculating the position of the object from a consideration of said magnetic interaction and from the known magnetic parameters  
25 relating to said applied field and to said small piece of magnetic material.

34. A method according to claim 33, characterised in that said object is a surgical instrument.  
30

35. A method according to claim 34, characterised in that said object is a surgical probe or needle.

36. A method according to claim 33, 34 or 35,  
35 characterised in that said small piece of high magnetic permeability magnetic material is in the form of a thin

-43-

foil, a wire or a thin film.

37. A method according to any one of claims 33 to 36,  
characterised in that said magnetic field sources are  
5 coils.

38. A method according to any one of claims 33 to 36,  
characterised in that one or both of said magnetic  
field sources is/are permanent magnet(s).

10 39. A method according to any one of claims 33 to 38,  
characterised in that the applied magnetic field is  
generated by three sets of mutually orthogonal magnetic  
field sources.

15 40. A method according to claim 38 or 39,  
characterised in that the applied magnetic field is  
generated by operating sequential field scans and  
calculating, for each scan, the position of the centre  
20 of the harmonic output from the magnetic material.

41. A method according to claim 40, characterised in  
that there are nine sequential field scans, operated  
according to the following table, in which the magnetic  
25 field sources are identified as a, b and c and the  
scans are numbered from 1-9 (scanning order being of no  
significance):

30

Orthogonal field source	1	2	3	4	5	6	7	8	9
a	ON	ON	ON	OFF	OFF	ON	OFF	OFF	ON
b	OFF	ON	OFF	ON	ON	ON	OFF	ON	OFF
c	OFF	OFF	ON	OFF	ON	OFF	ON	ON	ON

35

-44-

42. A method according to claim 40, characterised in that three orthogonal coil sets are continuously excited so as to create a continuously rotating field direction which covers the volume of interest in  
5 controlled sweeps of predetermined width.

43. A method of coding and/or labelling individual articles within a predetermined set of articles by means of data characteristic of the articles, e.g.  
10 article price and/or the nature of the goods constituting the articles, which method is characterised by applying to each article a magnetic tag or marker carrying a predetermined arrangement of magnetic zones unique to that article or to that  
15 article and others sharing the same characteristic, e.g. article price and/or the nature of the goods constituting the article, said magnetic tag or marker being susceptible to interrogation by an applied magnetic field to generate a response indicative of the  
20 magnetic properties of the tag or marker and hence indicative of the nature of the article carrying the magnetic tag or marker.

44. A method according to claim 43, characterised in  
25 that said magnetic tag or marker comprises a plurality of magnetic zones each displaying high permeability.


45. A method according to claim 44, characterised in that each magnetic zone can be magnetically biased by  
30 means of a second layer of medium-coercivity magnetic material.

46. A method of totalising data (e.g. prices) from an assembly of individual articles each carrying a  
35 magnetic tag as claimed in any one of claims 1 to 11, the tags carrying data representative of a specific

-45-

characteristic (e.g. price) of the article to which they are attached, characterised in that the assembly of articles is caused to move through an interrogation zone where the assembly is subjected to a method as  
5 claimed in any one of claims 39 to 42; and processing the signals received during said method to generate the required summing of individual datum values.

**Fig 1: Basic configuration for system using 2 Tx coils**



Tx Coil1, Tx Coil 2 typically 45cm x 45cm, each 450 turns 0.56mm wire.


Tx1, Tx2 separation  $\sim 20$ cm

Typical current  $I = 3$ Amp,  $i = 50$ mA.

At mid-point plane between coils, field in x direction is zero (with no AC bias applied)




**Fig 2: Simple circuit for providing opposed DC fields and combined AC fields**




3/12

**Fig 3: Signals from tag at different positions with respect to null plane**




**Fig 4: Useful null regions around a permanent magnet**



A simple bar-magnet has regions near to its poles where narrow null planes exist for tags with their sensitive axes aligned orthogonal to X-Y. Paths A-B or C-D can be used as the basis of a simple interrogator.


**Fig 5: Conceptual coil and permanent magnet arrangement for simple tag reader**



Tags may pass either through coil (path C-D) or over coil Path A-B)

Tags must be oriented with their magnetic axis in the direction of the tag movement

**Fig 6: One example of how a pair of permanent magnets may be used to create a null plane**



7/12

**Fig 7: Simple loop reader head using permanent magnets to create null plane**







Fig 8: Typical interrogator system



9/12

**Fig 9: Examples of formats for multi-bit tags****a) Simple linear tag using discrete magnetic elements****Alternative using strip or wire material****Examples shown are basic 6-bit tags, coded 111101**






**Fig 9: Examples of formats for multi-bit tags****b) One method of making simple linear tags using continuous magnetic elements****Typical detected output from reader (ADC Input)**

Fig. 9d.

## Fig 9: Examples of formats for multi-bit tags


### c) One possible arrangement for 2 dimensional tags

Position where discrete element may be placed, or  
high permeability region can be defined  
(magnetically, using bias layer or by other methods)



16-bit Tag

12/12

**Fig 10: 3-D location system for surgical applications**

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 96/00823

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 G01V15/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G01V

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO,A,89 06810 (SCIENT GENERICS LTD) 27 July 1989	1-3,9
A	see abstract; claims 1,2,5,6,9 see page 3, line 8 - page 4, line 17 ---	6,7,12
X	IEEE TRANSACTIONS ON MAGNETICS, vol. 17, no. 6, November 1981, NEW YORK US, pages 2988-2990, XP002008885 G.COUDERCHON E.A.: "Principles of a magnetic method for labelling moving targets" see page 2988, column 1, line 29 - line 54 see page 2990, column 1, line 6 - column 2, line 44 --- -/--	1,4,6, 12, 15-18, 22,29,32

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

19 July 1996

Date of mailing of the international search report

26.07.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Haasbroek, J

# INTERNATIONAL SEARCH REPORT

National Application No

PCT/GB 96/00823

## C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 295 028 (SCIENT GENERICS LTD) 14 December 1988	1-4,6,9, 10
Y	see page 1, line 16 - line 40  see page 3, line 2 - line 57 see page 5, line 32 - line 57 see page 7, line 36 - line 51 see page 9, line 37 - line 58 see claims 1-13,47,48 ---	12, 14-17, 22,29,32
Y	US,A,4 663 612 (MEJIA EZEQUIEL ET AL) 5 May 1987  see abstract; claims 1,6,8; figure 6 see column 1, line 11 - line 34 see column 9, line 11 - column 10, line 2 see column 10, line 62 - column 11, line 14 ---	12, 14-17, 22,29,32
A	US,A,5 017 907 (CORDERY ROBERT A ET AL) 21 May 1991  see abstract; figures 2,3,5,6 see column 1, line 41 - line 68 see column 3, line 3 - line 57 ---	16,18, 22,24, 27,28
A	US,A,4 751 516 (LICHTBLAU GEORGE J) 14 June 1988 see abstract -----	12,15

# INTERNATIONAL SEARCH REPORT

information on patent family members

National Application No

PCT/GB 96/00823

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8906810	27-07-89	AU-B- 2931889	11-08-89
EP-A-0295028	14-12-88	AU-B- 613045	25-07-91
		AU-B- 1746388	08-12-88
		CA-A- 1291244	22-10-91
		DE-A- 3880202	19-05-93
		EP-A- 0295085	14-12-88
		WO-A- 8809979	15-12-88
		JP-A- 1064207	10-03-89
		JP-T- 1503577	30-11-89
		US-A- 4960651	02-10-90
		US-A- 4940966	10-07-90
US-A-4663612	05-05-87	CA-A- 1234892	05-04-88
		CH-A- 668845	31-01-89
		DE-A- 3505052	22-08-85
		FR-A- 2559914	23-08-85
		GB-A,B 2154396	04-09-85
		JP-A- 60193098	01-10-85
		NL-A- 8500440	16-09-85
		SE-A- 8500652	17-08-85
US-A-5017907	21-05-91	CA-A- 2034045	17-07-91
US-A-4751516	14-06-88	EP-A- 0386134	12-09-90
		WO-A- 8912916	28-12-89
		US-A- 4866455	12-09-89

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**